



DECLARATION OF PERFORMANCE

No. 001_ITALGRANITI

1. *Unique identification code of the product type:*
Type, batch or serial number or any other element allowing identification of the product:
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$
2. *Intended use(s):*
For internal and external walls and floorings.
3. *Name or registered trade mark, and contact address of the manufacturer:*
ITALGRANITI GROUP SPA
Via Radici in Piano, 355 – 41043 Casinalbo di Formigine (MO) – Italy
Tel. 0039 059 888411 Fax 0039 059 848808 P. iva e CF 03294200369
info@italgranitigroup.com www.italgranitigroup.com
4. *System(s) of assessment and verification of constancy of performance (AVCP)*
System 4
5. *Name and identification number of notified laboratory, if relevant: N.A.*
Task(s) carried out: N.A.
AVCP system: N.A.
Document issued and date of issue: N.A.
6. *Declared performances:*

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1+A1 _{fl}	EN 14411:2012
Release of dangerous substance, for	NPD	
• Cadmium	NPD	
• Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness, as:	See table attached	
Tactility	NPD	
Bond strength/adhesion, for	≥ 1 N/mm ²	
Cementitious adhesive, type C2		
Thermal shock resistance	Pass	
Durability for:		
• internal use	Pass	
• external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function
Dott. Ing. Antonio Tartaglia
Technical Manager


ITALGRANITI GROUP S.p.A.
Via Radici in Piano, 355
41043 CASINALBO DI FORMIGINE (MO)
C.F./P. IVA 03294200369

Place and date of issue

Casinalbo, 2016-11-01

This documents of performance does not include decorative accessories , trim and mosaic



Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Anhang der Leistungserklärung
Annexe à la Déclaration de Performance
Anexo a la Declaración de Performance
No. 001_ITALGRANITI

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Tabelle - Rutschfestigkeit (soweit durch Rechtsverordnung erforderlich)
Tableau - Glissement (si requis par la réglementation)
Tabla - Deslizamiento (donde sea requerido por ley)

Rev.07 del /of/vom/de/de 11/01/2016

MARCHIO / BRAND / MARQUE / MARKE / MARCA

ITALGRANITI

Serie / Series / Kollektion / Série / Serie	Superficie / Surface finishes / Oberflächen / Surfaces / Superficies	DIN 51130 (DE)	BCRA D.M. 236/1989 (IT)	Regolamento basico SU 3/2006 (ES)	CEN/TS 16165:2012 Annex B α_{SHOD} (F)
LISTONE D	NATURALE	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	ANTISLIP	R11	> 0,40	35 < Rd ≤ 45	α da 20° a 27°
MATERIA D	NATURALE (Tecno +Fusion)	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	NATURALE (Forma)	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
	ANTISLIP	R11	> 0,40	Rd > 45	α da 20° a 27°
MINERAL D	NATURALE	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
	ANTISLIP	R11	> 0,40	35 < Rd ≤ 45	α da 20° a 27°
	LAPPATO	NPD	NPD	NPD	NPD
NATURAL STONE	NATURALE	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	LAPPATO	NPD	NPD	NPD	NPD
	BOCCIARDATO	R11	> 0,40	Rd > 45	α da 20° a 27°
STONE D	NATURALE	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	ANTISLIP	R11	> 0,40	Rd > 45	α da 20° a 27°
STONE MIX	NATURALE	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	ANTISLIP	R11	> 0,40	Rd > 45	α da 20° a 27°
SCRAPWOOD	NATURALE	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
MAXIWOOD	NATURALE	R9	NPD	15 < Rd ≤ 35	α da 6° a 10°
	LAPPATO	NPD	NPD	NPD	NPD
STONE PLAN	NATURALE	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
	ANTISLIP	R11	> 0,40	35 < Rd ≤ 45	α da 20° a 27°
WHITE EXPERIENCE	NATURALE	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	ANTICATO	R9	> 0,40	15 < Rd ≤ 35	α da 6° a 10°
	RULLATO	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
	BOCCIARDATO ANTISLIP	R11	> 0,40	Rd > 45	α da 20° a 27°
	LAPPATO	NPD	NPD	NPD	NPD
	SPAZZOLATO	NPD	NPD	NPD	NPD
STONE AGE	NATURALE	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
SQUARE	NATURALE	R10	> 0,40	15 < Rd ≤ 35	α da 11° a 19°
	LAPPATO	NPD	NPD	NPD	NPD



BEIGE EXPERIENCE	NATURALE	R9	> 0,40	$15 < Rd \leq 35$	α da 6° a 10°
	ANTICATO	R9	> 0,40	$15 < Rd \leq 35$	α da 6° a 10°
	RULLATO	R10	> 0,40	$15 < Rd \leq 35$	α da 11° a 19°
	BOCCIARDATO ANTISLIP	R11	> 0,40	$Rd > 45$	α da 20° a 27°
	LAPPATO	NPD	NPD	NPD	NPD
	SPAZZOLATO	NPD	NPD	NPD	NPD
MY PLANK	NATURALE	R9	> 0,40	$15 < Rd \leq 35$	α da 6° a 10°
	TEXTURE	R10	> 0,40	$15 < Rd \leq 35$	α da 11° a 19°
URBANA CONTRACT	NATURALE	NPD	> 0,40	$15 < Rd \leq 35$	NPD
SPATULA	NATURALE	R10	> 0,40	$15 < Rd \leq 35$	α da 11° a 19°
	LAPPATO	NPD	NPD	NPD	NPD
SANDS EXPERIENCE	NATURALE	R10	> 0,40	$15 < Rd \leq 35$	α da 11° a 19°
	BOCCIARDATO	R10	> 0,40	$15 < Rd \leq 35$	α da 11° a 19°
	ONDA	NPD	NPD	NPD	NPD
	RIGATO	NPD	NPD	NPD	NPD
	LAPPATO	NPD	NPD	NPD	NPD
NORDIC STONE	NATURALE	R9	> 0,40	$15 < Rd \leq 35$	α da 6° a 10°
ALNUS	NATURALE	NPD	NPD	NPD	NPD
METROPOLI	NATURALE	NPD	NPD	NPD	NPD
MARMI IMPERIALI	LAPPATO	NPD	NPD	NPD	NPD
MARMO D	NATURALE	R9	> 0,40	NPD	NPD
	LAPPATO	NPD	NPD	NPD	NPD
OUTFLOOR20	ANTISLIP	R11	> 0,40	$35 < Rd \leq 45$	α da 20° a 27°



**MARCATURA CE
CE MARKING
CE-KENNZEICHNUNG
MARQUAGE CE
MARCADO CE**

CE

ITALGRANITI GROUP SpA

Via Radici in Piano, 355 – 41043 Casinalbo di Formigine (MO) - Italy

05

001_ITALGRANITI

EN 14411:2012

Dry-pressed ceramic tiles, with water absorption
 $E_b \leq 0,5\%$, for internal and external walls and floorings