

## CE CONFORMITY DECLARATION

### Gold Art Ceramica Spa

Division **Energie Ker**

Via Giardini Nord, 231/233, 41026, Pavullo n/F (Mo) Italy,  
factories located at:

41026 - Pavullo (Mo) Italy, Via Giardini Nord, 231/233, **0011**

41026 - Pavullo (Mo) Italy, Via Giardini Nord, 231/233, **0012**

manufacturer of :

glazed and unglazed floors and walls ceramic tiles **Energie Ker** dry pressed ,  
EN 14411, Gruppo B I a, 0.5 <E< 3%, S.4,

10 cm x 30 cm x 9 mm	UGL/GL
15 cm x 30 cm x (8.2 mm – 9.2 mm)	UGL/GL
20 cm x 20 cm x (7.2 mm- 11 mm – 12 mm – 14 mm)	UGL/GL
20 cm x 50 cm x 9 mm	UGL/GL
20 cm x 60 cm x 9 mm	UGL/GL
30 cm x 30 cm x(7.2 mm - 8.2 mm – 11 mm – 12 mm)	UGL/GL
30.8 cm x 30 8 cm x 8.2 mm	UGL/GL
17.9 cm x 35.8 cm x 9.2 mm	UGL/GL
35.8 cm x 35.8 cm x ( 7.7 mm- 9.2 mm)	UGL/GL
45 cm x 45 cm x 9 mm	UGL/GL
45.5 cm x45.5 cm x ( 8 mm - 9 mm)	UGL/GL
51 cm x 51 cm x 9 mm	UGL/GL
60 cm x 30 cm x 9 mm	UGL/GL
30.4 cm x 61 cm x 9 mm	UGL/GL
30.8 cm x 61.5 cm x 9 mm	UGL/GL
15.2 cm x 61.5 cm x 9 mm	UGL/GL
60 cm x 60 cm (9 mm-12 mm-20 mm)	UGL/GL
61 cm x 61 cm x 9 mm	UGL/GL
61.5 cm x 61.5 cm x 9 mm	UGL/GL
15 cm x 90 cm 9 mm	UGL/GL
30 cm x 90 cm x 9 mm	UGL/GL
45 cm x 90 cm x 9 mm	UGL/GL
90 cm x 90 cm x 9 mm	UGL/GL
20 cm x120 cm x 9 mm	UGL/GL
20 cm x 121 cm x (9 mm-20 mm)	UGL/GL
30 cm x 121 cm x (9 mm- 20 mm)	UGL/GL
60 cm x 120 cm x ( 9 mm- 20 mm)	UGL/GL
61 cm x 121 cm x (9 mm- 20 mm)	UGL/GL
120 cm x 120 cm x (9 mm- 20 mm )	UGL/GL
121 cm x 121 cm x (9 mm- 20 mm)	UGL/GL
20 cm x 180 cm x 9 mm	UGL/GL
30 cm x 180 cm x 9 mm	UGL/GL
40 cm x 180 cm x 9 mm	UGL/GL
80 cm x 180 cm x 9 mm	UGL/GL
120 cm x 270 cm x (6 mm)	UGL/GL
121 cm x 270 cm x ( 6 mm)	UGL/GL
160 cm x 320 cm x ( 6 mm – 12 mm)	UGL/GL
163 cm x 324 cm x 12 cm	UGL/GL

having the following technical characteristics:

characteristics	declared values i	test method
Fire resistance	Class A1	Without test
Flexion resistance	Breaking strength >1300 N Flexion resistance >35 N/mm <sup>2</sup>	EN ISO 10545-4 EN ISO 10545-4
Resistance to thermal shock Durability- frost defrost resistance	Resistant Resistant	
yield of harmful substances	Migration of cadniun 0.0 mg/dm <sup>2</sup> Migration of lead 0.0 mg/mm <sup>2</sup>	
Slip resistance	N.P.D. N.P.D.	EN 10545-15 EN 10545-15
		DM 236/89 DIN 51130

Declares that the ceramic tiles produced under **Energie Ker** Division comply with the technical characteristics required by EN 14411 annex ZA.

The tests on the ceramic tiles **Energie Ker** are effected by our internal laboratories .

Our ceramic tiles **Energie ker** are manufactured with natural raw materials, sands, kaolins, feldspars and clays mixed in adequate quantities. They can be used for wall and floor utilizing glues or sand and concrete.

Pavullo, 21 Novembre 2019

Firma del Legale rappresentante S.p.A.  
 GOLDART CERAMICHE S.p.A.  
 Via Giardino Nord 231/233  
 41028 Pavullo nel Frignano (MO)  
 Tel 0536 301711 Fax 0536 301764  
 Cod. Fisc. 01193700357  
 P I V A 0 1 7 2 1 8 9 0 3 6 4